



Rechargeable Battery Counting Scale









Feature:

- ALH4 up to 1/30,000 display resolution (Internal resolution 1/600,000)
- High speed 24bits AD; Display reading speed faster
- Faster weighing stability
- Faster zero return
- Zero key and Tare key react faster
- LCD display full tare (Weight-6digits, Unit Weight-6 digits, Quantity-6 digits)
- 10 preset unit weight function
- Auto calibration function, OL protection
- Weight and quantity over-limit warning
- Auto average unit weight, pre-tare function
- Kilogram(kg), pound(lb) weighing modes
- Stable sampling range setting function
- Data accumulations (weight and quantity)
- Low power and charging status indication
- Built-in rechargeable battery
- Easily adjusted leveling feet for stability of the scale



Option:

- RS232: Bidirectional transmission for easy data reading or printing
- RS232-F: Free form card (include Real Time Clock)
- OIML approved model available for 1/3 000 display resolution
- 1/30,000 with temperature compensation component more accurate and stable

Specifications:

Model	Capacity	Division	Resolution
ALH 4 - 1.5	1.5 kg (3 lb)	0.1 g (0.0002 lb)	1/15,000
ALH 4 - 3	3 kg (6 lb)	0.2 g (0.0005 lb)	1/15,000
		0.1 g (0.0002 lb)	1/30,000
ALH 4 - 6	6 kg (12 lb)	0.2 g (0.0005 lb)	1/30,000
ALH 4 – 7.5	7.5 kg (15 lb)	0.5 g (0.001 lb)	1/15,000
ALH 4 - 15	15 kg (30 lb)	1 g (0.002 lb)	1/15,000
		0.5 g (0.001 lb)	1/30,000
ALH 4 - 30	30 kg (60 lb)	2 g (0.005 lb)	1/15,000
		1 g (0.002 lb)	1/30,000

Operating Temperature: -10°C ~ 40°C (14°F ~ 104°F); Approval Model: -10°C ~ 40°C (14°F ~ 104°F)

Power Source: AC 100V~240V (±10%) + DC 6V/4Ah rechargeable battery

Dimensions: $275 \times 105 \times 310 \text{ mm} (W \times H \times D)$

Platter Size: 280 × 230 mm (W x D)

Display: LCD. 6, 6, 6 Digits, Height 14 mm, LED Backlight



EXCELL PRECISION CO., LTD.

6F, No.127, Lane 235, Baoqiao Rd., Xindian Dist., New Taipei City 23145, Taiwan

Tel: +886-2-89191000 Website: www.excell-scale.com Fax: +886-2-89191177 Website: www.excell-scale.com.tw