

QHW Weighing Scale



Features

Easy to move: battery operation, compact, light weight construction, it is suitable for the use in several locations (production, warehouse, logistic department etc.).

Easy to clean: stainless steel pan. Its smooth surfaces make it simple to clean

Easy to read: 6 digits 24mm digits high LCD display, with white color LED backlight

High precision: external resolution up to 1/150,000

Full function: unit change, accumulation, checkweighing, simply counting, percentage weighing.

Check weighing: a visual and sound signal helps with portioning, dispensing or grading

Technical Data

Display: LCD display, digit height 24 mm, with white color LED backlight

Power: AC adapter (100~240VAC/12V500mA), lead acid battery (6V/4Ah), operation time: 70 hours

Dimensions 315(W)×349.9(D)×118.5(H)mm

Pan size: 230×300 mm

Net weight: 2.89kg


Gross weight: 4.22kg

Operation temperature: -10°C~40°C


Accessories

- Rear display
- RS-232 interface can connect to PC or printer.
- RS-232 cable for PC
- RS-232 cable for printer
- Label printer
- Mini printer
- 3 color light tower

Standard



Factory Option



Model	Weighing Capacity [Max]kg	Readability [d]g	Verification value [e]g	Minimal load [Min]g
QHW-3K	3	0.1	/	2
QHW-6K	6	0.2	/	4
QHW-15K	15	0.5	/	10
QHW-30K	30	1	/	20
QHW+-3K	3	0.05	/	1
QHW+-6K	6	0.1	/	2
QHW+-15K	15	0.2	/	4
QHW+-30K	30	0.5	/	10
QHW++-3K	3	0.02	/	0.4
QHW++-6K	6	0.05	/	1
QHW++-15K	15	0.1	/	2
QHW++-30K	30	0.2	/	4
QHW-3K-M	3	1	1	20
QHW-6K-M	6	2	2	40
QHW-15K-M	15	5	5	100
QHW-30K-M	30	10	10	200
QHW-6K-MR	6	1/2	1/2	20
QHW-15K-MR	15	2/5	2/5	40
QHW-30K-MR	30	5/10	5/10	100